



GENESIS SERIES CABLE

Coaxial Cable Part No. 5001

Description: 20 AWG RG59/U COAX CABLE
Compliance: UL13

Construction:

Conductor 20 AWG Solid Bare Copper

Insulation

Type Foamed Polyethylene
Color White
Thickness 0.057" nom.
Diameter 0.145" nom"

Braid

Strands 0.005" nom. Bare Copper
% Coverage 95 nom.

Jacket

Type PVC
Color Black, White
Thickness 0.034" nom.
Diameter 0.242" nom.

Legend (Ink Print) HONEYWELL P/N 5001 RG 59/U 20 AWG CCTV PREMIUM 3038058 (ETL) TYPE CL2 75C SUNRES
W/O# XXXXXX-XXX XXXX FT (RoHS) CAMERA/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Packaging

Properties

Temperature Rating -20 to 75 °C
Voltage Rating 300 Volts
Capacitance 17 pf/ft nom.
Impedance 75 Ohms nom.
Resistance 10.9 Ohms/M' at 20°C
Attenuation (db/100') -0.37 at 1 MHz, -6.2 at 400 MHz, -9.90 at 1000 MHz
Flame Ratings UL 1685 Vertical Tray Flame